

## Why **NCR** Orderman?

Orderman GmbH is part of the global NCR Corporation. With its premium products, the Salzburg based company is the leading provider of technology solutions for the European hospitality industry. Handhelds, POS systems, and services from Orderman are used worldwide in more than 55,000

restaurants. Innovative technology combined with a unique user experience and an emotionally strong design have made Orderman a global leader and a synonym for mobile technology in the hospitality industry. Every day 25 additional restaurants choose Orderman.

Visit [www.orderman.com](http://www.orderman.com) for more information



### **ORDERMAN GmbH**

Bachstrasse 59  
5023 Salzburg, Austria  
Tel.: +43/662/65 05 61-0  
Fax: +43/662/65 05 61-819  
[sales@orderman.com](mailto:sales@orderman.com)  
[www.orderman.com](http://www.orderman.com)

## **NCR** **CX3** / All-in-One POS

The NCR CX3 all-in-one POS offers excellent performance and sleek design in a cost-effective solution. Its durable construction and the unique Orderman warranty guarantee a long service life.

Subject to technical modifications in the interest of progress. The models displayed may vary based on country requirements. Orderman GmbH reserves the right to modify system design and/or features. Technical descriptions quoted may not be used as a basis for a sales agreement. We cannot be held liable for print errors.

© 2021 NCR Corporation Patents Pending [ncr.com](http://ncr.com)



Visit [orderman.com](http://orderman.com) for more information,  
or e-mail: [sales@orderman.com](mailto:sales@orderman.com).



# Your professional restaurant device.

The latest generation of Orderman POS systems offers tried and tested Orderman quality, flexible options, and state-of-the-art technology at a great price-performance ratio. NCR CX3 was developed exclusively for everyday use in the restaurant industry – and it shows with every touch.

Thanks to its powerful performance, everything runs even more smoothly than before. Because the CX3 was designed to be energy efficient, however, it uses very little power. The durable metal housing also guarantees a long service life – NCR CX3 is virtually indestructible. What makes this cash register perfect for any restaurant business is the wide range of Orderman accessories that are unique to the Orderman brand, such as the popular 2-in1 waiter's lock in both Addimat and Dallas format. The simple wall mount option makes the NCR CX3 an even more flexible tool for your business.

## CX3 Highlights

- ▶ Purpose-built for the restaurant industry
- ▶ Metal housing guarantees durability
- ▶ Especially energy efficient thanks to mobile processors
- ▶ Fan-less with the latest technology
- ▶ Unique accessories for individual requirements
- ▶ Up to 5 years Care Gold warranty



## Technical Details



MODEL SPECS	
Chipset	Whiskey Lake-U
Prozessor	Celeron® 4205U, 1.80GHz Core™ i3-8145UE, 2.20 GHz (Turbo 3.9GHz)
Cache	2MB 4MB
Cores / Threads	2/0 2/2
Thermal Design Power	15 Watts / fanless
Memory	1 x 8 GB DDR4-2133, SODIMM 1 x 8 GB DDR4-2400, SODIMM
SSD - Solid State Drive	120GB SSD M.2 SATA
Integrated Touch Display	15.6" Projected Capacitive, 16:9 1366 x 768 10-point touch
Brightness	350 nits
VESA pattern	75mm

CONNECTIVITY	
Serial	2 x RJ45 serial (12V/5V, 1A max)
USB	6 x USB Total 2 x USB 3.0 (+5V at 0.9A max.), 4 x USB 2.0 (+5V at 0.5A max.)
Display	1 x DisplayPort
Cash Drawer	1 x RJ12 Cash Drawer 24V (12V/24V dual with y-cable)
Ethernet	1 x LAN
Power Button / Power LED	Yes

SUPPORTED OPERATING SYSTEM	
Operating System	Windows 10 IoT Enterprise 2019 LTSC
Image Recovery	Yes

PERIPHERALS	
Integrated 2in1 SignIn for Addimat and Dallas Key	Option + Photo
Integrated Biometric Reader	Option + Photo
3-track Encrypted MSR	Option + Photo
Integrated Speaker	Internal Buzzer for Beep

CUSTOMER DISPLAYS	
Integrated APA customer display	Option + Photo
10" Color LCD (Touch or Non-touch)	No integrated option – remote from terminal option

OTHER	
Terminal dimensions	380.2 mm x 210.6 mm x 299.1 mm
Weight	6,06 kg. Note: Weight varies by configuration
Operating Range	10-40°C / 20-80% relative humidity
Storage and Transit Range	-15 to 60°C / 10-90% relative humidity
Certificate	CE, FCC, UKCA